



Basic Information

| | |
|----------------------|--|
| Embedded Parts | With Trim/Trimless |
| Mounting | Recessed |
| Trim Finishing Color | White/Black |
| Reflector Color | White/Black/Golden |
| Material | Cold Forged Pure Alu. (Heat Sink)/Die-casting Alu. |
| Cutout Size | L148*75mm/L148*148mm |
| Light Direction | 25° 360° |
| IP Rating | IP20 |
| Power | Max. 2*15W/4*15W |
| Input Voltage | DC36V |
| Input Current | Max. 2*350mA/4*350mA |

Optical Parameters

| | |
|-----------------|-------------------------|
| Light Source | LED COB |
| Lumens | 65lm/W 90lm/W |
| CRI | 97Ra / 90Ra |
| CCT | 3000K 3500K 4000K |
| CCT Changeable | 2700K 6000K 1800K 3000K |
| Beam Angle | 15° 25° 35° 50° |
| Shielding Angle | 50° |
| UGR | < 13 |
| LED Lifespan | 50000hrs |

| | |
|----------------|--|
| Driver Voltage | AC100-120V AC220-240V |
| Driver Options | ON/OFF DIM TRIAC/ PHASE-CUT DIM 0/1-10V DIM DALI |

